



## M490G

Electromagnetic gate lock



### Overview

The Schlage M490G electromagnetic gate lock is a weather resistant electromagnetic lock with 1500 lbs of holding force, designed for use on all types of sliding and swinging gates. As a high security magnetic lock, it can accommodate misalignment problems while supplying superior holding force.

A 1/2" compression connector is provided for installation of 1/2" EMT conduit, insuring protection of hook-up wiring from weather and vandalism. Heavy-duty plating resists corrosion of mating surfaces, providing a low maintenance locking device.

A modified top jamb mounting bracket allows a single M490G to be mounted in a variety of positions. The M490G gate lock may be mounted to any gate frame or post. Special brackets may be required to adapt the lock to a particular frame or post. It is important that the lock is mounted so that the armature pulls straight back from the magnet face.

The M490G can be field configured for either 12 or 24 VDC operation. Magnetic Bond Sensor (MBS) and Gate Status Monitor (DPS) are standard.

### Features and benefits

- 1500 lbs of direct holding force
- Magnetic Bond Sensor (MBS) and Gate Status Monitor (DPS)
- Field selectable 12 or 24VDC operation
- Built-in voltage spike suppressor
- Electroless nickel plated finish
- Universal mounting brackets
- 1/2" EMT compression fitting
- Two foot wire leads
- Weather resistant for exterior use
- Accomodates gate misalignment
- No moving parts - low maintenance

## Standard features

### M490G

- Magnetic Bond Sensor (MBS) monitors the strength of the bond between the lock and armature so you know the door is secure
- Door Position Switch (DPS) monitors whether the door is open or closed
- Universal Mounting Brackets for swinging or sliding gate applications
- Built-in voltage spike suppression
- 1/2" EMT compression fitting
- Special corrosion resistant plating

## M490G electromagnetic gate lock specifications

Specifications	M490/M490G
Holding force	Meets or exceeds BHMA standard of 1500 lbs
Input voltage (field selectable)	12/24 VDC
Current draw (amps standard unit)	.65A @ 12 VDC .35A @ 24 VDC
Height	3"
Length	11"
Width	1 3/4"
Weight (approximates)	14 lbs
Temperature	0° - 49° C (32° - 120° F)
Wire gauge	14-22 AWG

## Filler plates

Electromagnetic lock	M490G
Length	9"
Width x Height	Plate no.
1 1/4" x 1/8"	49G1F
1 1/4" x 1/4"	49G2F
1 1/4" x 3/8"	49G3F
1 1/4" x 1/2"	49G4F
1 1/4" x 5/8"	49G5F
1 1/4" x 3/4"	49G6F
3/4" x 1/2"	49G7F
3/4" x 5/8"	49G8F

## Angle brackets

Electromagnetic lock	M490G
Length	9"
Width x Height	Bracket no.
1" x 1"	49G1A
1 1/2" x 1"	49G2A
1 1/2" x 1 1/2"	49G3A
1 1/2" x 2"	49G4A
1 1/2" x 2 1/2"	49G5A

Allegion, the Allegion logo, Schlage, and the Schlage logo are trademarks of Allegion plc, its subsidiaries and/or affiliates in the United States and other countries. All other trademarks are the property of their respective owners.

## About Allegion

Allegion (NYSE: ALLE) creates peace of mind by pioneering safety and security. As a \$2 billion provider of security solutions for homes and businesses, Allegion employs more than 7,800 people and sells products in more than 120 countries across the world. Allegion comprises 23 global brands, including strategic brands CISA®, Interflex®, LCN®, Schlage® and Von Duprin®. For more, visit [www.allegion.com](http://www.allegion.com).

aptiQ ■ LCN ■  ■ STEELCRAFT ■ VON DUPRIN



© 2014 Allegion  
004158, Rev. 02/14  
[www.allegion.com/us](http://www.allegion.com/us)